DLCM Tools Guide

Table of Contents

1. Tool Options 2
   1.1. `load` function 2
   1.2. `local-load` function 2
   1.3. `check` function 2
   1.4. `import` function 2
   1.5. `git` function 2
2. Installation 3
   2.1. Get the tool 3
   2.2. Organize the data 4
3. Execution 6

DLCM Tools **v3.1.9**, *2026-07-20*

The current documentation is available in HTML or PDF.

Chapter 1. Tool Options

1.1. `load` function

This function allows to add data files to an existing deposit, identified by `<Deposit ResId>`.

For each deposit, the tool will crawl the corresponding folder of the deposit and upload each file as a data file in the correct folder (i.e. `relative location`).

The upload volume is limited. Generally, the limitation is up to 1GB: : ask to administrator of the service.

1.2. `local-load` function

This function is equivalent the `load` one by referencing files instead of uploading them.

It is recommended for big files, greater than 1GB.

The prerequisite is to transfer files on `pre-ingest` machine, before to run the tool.

1.3. `check` function

This function allows to verify if there is the same number of files by comparing the folder on disk and the deposit.

1.4. `import` function

This function allows:

1. To create an organizational unit, if it does not exist. The control criterion is the name of organizational unit
2. To create a deposit with the folder name as title
3. To add data files by uploading files with relative location

1.5. `git` function

This function allows to create a deposit and to add data files from a GIT repository.

The extraction is based on a branch or a tag or a commit.

Chapter 2. Installation

2.1. Get the tool

- Download the DLCM tool package: DLCM-Tools-3.1.9.jar
- Define the properties file

dlcm-tools.properties

```
##############################################
# 'load' 'local-load' & 'check' parameter    #  ①
# Folder where the data to load or check are #
##############################################
dlcm.load=<Must be defined>

########################################
# 'import' parameter                   # ②
# Folder where the data to import are #
########################################
dlcm.import=<Must be defined>

####################
# 'git' parameters # ③
####################
dlcm.git.organizational-unit=<To be defined>
# Example: dlcm.git.organizational-unit=DLCM
dlcm.git.repository-url=<Must be defined>
# Example: dlcm.git.repository-url=git@gitlab.unige.ch:solidify/solidify-tools.git
dlcm.git.branch=<Could be defined, optional>
# Example: dlcm.git.branch=1.3-maintenance
dlcm.git.commit=<Could be defined, optional>
# Example: dlcm.git.commit=729a871d
dlcm.git.tag=<Could be defined, optional>
# Example: dlcm.git.tag=dlcm-1.3.1
#------------------#
# Could be changed #
#------------------#
dlcm.git.data-category=Software
dlcm.git.data-sub-category=Code

########################################
# 'purge' parameters                   # ④
# List of relative locations to purge #
########################################
dlcm.load=<Must be defined>
dlcm.relative-locations=<Must be defined>
# Example to purge all data files: dlcm.relative-locations=/
# Example to purge data files in images & old: dlcm.relative-locations=/images,/old
```

```
################################################################
# Profile to determine which function to run                   #
#  - load = To upload data files in existing deposits          #
#  - check = To check between file system & existing deposits  #
#  - import = To create deposit and to upload data files       #
#  - git = To import data files from GIT repository            #
################################################################
spring.profiles.active=<Must be defined> ⑤
# Examples:
#  spring.profiles.active=load
#  spring.profiles.active=import,git

# DLCM modules
dlcm.module.admin.url=<DLCM Admin module URL: must be defined>
# Example: dlcm.module.admin.url=https://sandbox.dlcm.ch/administration/admin
dlcm.module.preingest.url=<DLCM Preingest module URL: must be defined>
# Example: dlcm.module.preingest.url=https://sandbox.dlcm.ch/ingestion/preingest
dlcm.module.ingest.url=
# Example: dlcm.module.ingest.url=https://sandbox.dlcm.ch/ingestion/ingest
dlcm.module.archival-storage.urls=
# Example: dlcm.module.archival-
storage.urls=https://sandbox.dlcm.chstoragion/archival-storage

spring.cloud.config.enabled=false

# Client should not instantiate JDBC / Hibernate / JPA layer
spring.autoconfigure.exclude[0]=org.springframework.boot.autoconfigure.orm.jpa.Hiberna
teJpaAutoConfiguration
spring.autoconfigure.exclude[1]=org.springframework.boot.autoconfigure.jdbc.DataSource
AutoConfiguration
spring.autoconfigure.exclude[2]=org.springframework.boot.autoconfigure.jdbc.DataSource
TransactionManagerAutoConfiguration
spring.autoconfigure.exclude[3]=org.springframework.boot.autoconfigure.data.web.Spring
DataWebAutoConfiguration
```

① Parameters to upload/reference data files in existing deposits `or` to check between file system & existing deposits

② Parameters to create deposit and to upload data files

③ Parameters to import data files from GIT repository

④ Parameters to purge all data files in relative locations

⑤ Profiles to run tools: `load` / `local-load` / `check`/ `import` / `git` / `purge`

2.2. Organize the data

- The structure of the `import` folder must be like this:

`<Organisational Unit Name> / <Deposit Tile> / <Data Category> / <Data Type> / Your Data`

or

`<Organisational Unit Name> / <Deposit Tile> / Package / CustomMetadata / <Metadata Type resId> / Your Data`

- The structure of the `load` / `local-load` / `check` folder must be like this:

`<Deposit ResId> / <Data Category> / <Data Type> / Your Data`

or

`<Deposit ResId> / Package / CustomMetadata / <Metadata Type resId> / Your Data`

Data Category & Data Type values: see Data Categories & Types

Chapter 3. Execution

To run the tool:

- Set the environment variable to define OAuth2 access token

```
export OAUTH2_TOKEN=<OAuth2 Access Token>
```

- Run the following command

```
java -Dspring.cloud.bootstrap.location=<properties file>
-Dsolidify.oauth2.accesstoken=$OAUTH2_TOKEN -jar DLCM-Tools-3.1.9.jar >>dlcm-tools.log 2>&1
```